

## 516102 - 450MM X 2500M PRE-STRETCH MACHINE PALLETWRAP

Articel No.	45102500MWW		
Film Type	Blown Octene Linear Polyethylene Stretch Film. Pre-stretched with reinforced edges. Wound with oscillation. Cling outside. Clear Natural.		
Packaging:	54 Reels Unboxed. 3 layers/Pallet Pallet size: 800 X 1200 mm		
Dimensions:	Width:	450 mm	+/- 5%
	Thickness:	10 my	+/-5%*
	Length:	2500 m	+/- 5%
	Rollweight:	11,5 kg	+/- 5%
	Film weight net:	10,3 kg	+/- 5%
	* Roll edges = App. 20 my		
Core:	Inner Diameter:	76 mm	
	Length:	495 mm	
Copolymer:	Octene LLD/LD Polyethylene.		
REACH	LDPE/LLDPE film are not considered Substances of Very High Concern (SVHC) in the framework of REACH. Non of these substances is present in a concentration above 0,1 %. (ECHA List of SVHC candidates for authorization per 16 <sup>th</sup> June 2014).		

Typical film properties (before prestretched):

Property	Value	Unit	Test
Yield point (1)	9	MPa	ISO R-1184
Elongation (1)	12	%	ISO R-1184
Yield point (2)	16	MPa	ISO R-1184
Elongtion (2)	80	%	ISO R-1184
Tensile strength	42	N/mm2	BS-2782/326C
Ultimate elongation	550	%	BS-2782/326C
Dart Drop	170	g	BS-2782/352D
Prestretch	300	%	BS-2782/360B

Typical Values; not to be construed as specification limits.

Waste handling: The simple structure of polyethylene with its carbon and hydrogen atoms ensures that Carbon dioxide and Water are the sole combustion products.  
The film can be recycled to 100 percent.