



TECHNICAL SPECIFICATION

PVC PACKAGING TAPE

Backing Thickness	34-37 Micron
Total Thickness	55 Micron
Peel Adhesion	2.4 N/Cm
Tensile Strength	53 N/Cm
Elongation at break	60 %
Application Temperature	10 to 45 °C
Service Temperature	-25 to 65 °C

[Typical applications ▼](#)

Printable carton sealing PVC tape, suitable for manual dispenser application. Can be used for automated applications.

[Advantages and benefits ▼](#)

Excellent adhesion even in recycled cartons.

Excellent tack.

Long lasting adhesion.

No noise, silent unwinding.

Printable with vinyl inks.

Easy unwind and fast printability.

Once applied, ideal for storage in extreme temperature conditions and high moisture environments.

[Construction ▼](#)

Backing: Unplastified clear PVC film.

Adhesive: Natural rubber and hydrocarbon resins.

Color: Red, dark green, light

blue, white, orange, black,
yellow, fluoro orange.

[Storage ▼](#)

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

[Security ▼](#)

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.