


MASKING TAPE 4220

TECHNICAL DATA SHEET



DESCRIPTION:

Saturated semi-crepe paper masking tape coated with solvent based natural rubber adhesive. Suitable for all masking applications and light automotive use.

APPLICATIONS:

- · General masking
- Spray painting (automotive use suitable but not recommended)
- · Domestic DIY and Industrial general painting
- Holding sealing
- Fixing
- · Light duty packaging

PROPERTIES:

- Residue free removal
- Excellent tape to tape adhesion
- · Solvent and thinner resistant
- High initial tack
- · Easy tear
- Excellent conformability
- · Suitable for water and solvent based paints
- Easy curving
- · Easy application on uneven surfaces

ALL ABOUT TAPES



NOMINAL VALUES:

Backing

Impregnated Crepe Paper

Adhesive.

Solvent-based, Natural Rubber

Tensile Strength MD

85 ± 20 (N/25mm) | ~ 19 (lb/in) TM 5004 by Afera

Elongation at Break MD

8 ± 2 (%) TM 5004 by Afena

Peel Adhesion on Stainless Steel

Over 3.0 (N/25mm) | ~ 16 (oz/in) TM 5001 by Afera

Paper thickness

90 ± 15 (mic) | ~ 3,54 (mils)

Total thickness

105 ± 20 (mic) | ~ 4,53 (mils)

Application Range

General purpose, Non oven automotive application

Paper Colors White Sharp Yellow

Adhesive Color Transparent [2]