

PP Hot Melt 28my HM 702

TECHNICAL DATA SHEET

DESCRIPTION:

Hot melt based high adhesion synthetic rubber tape. Carrier BOPP 28mic film suitable for manual as well as automatic carton sealing line packaging applications.

APPLICATIONS:

- High tack adhesive for enhanced initial tack, and shear properties.
- Top line initial tack proves suitable for recycled cartons.
- Manual carton sealing.
- Automatic lines cartons sealing even of light cartons, due to easiness of unwinding and initial tack.
- Adhesion on uneven surfaces due to excellent adhesive power.
- Suitable for all sorts of packaging applications.

PROPERTIES:

- Increased initial tack
- Moisture compatible after application
- Instant adhesion
- Resistant to temperature changes
- Longevity of application

ALL ABOUT TAPES



NOMINAL VALUES:

Backing

Biaxially Oriented Polypropylene (BOPP)

Adhesive

Hot Melt (Solvent-free)

Tensile Strength MD

100 ± 20 (N/25mm) | ~ 22 (lb/in)
TM 5004 by Afera

Elongation at Break MD

140 ± 30 (%)
TM 5004 by Afera

Peel Adhesion on Stainless Steel

9 ± 2 (N/25mm) | ~ 33 (oz/in)
TM 5001 by Afera

Shear to Steel

Over 200 (h, 25mm x 25mm on stainless steel, 23°C)
TM 5012 by Afera

Film thickness

28 ± 1(mic) | ~ 1,10 (mils)

Film Colors Transparent

Adhesive Color Transparent Brown White